

## VARDI

### Exposed Single Lever Mini Valve EV

#### Product Specification

Product Code:	INSVEV0001
Finishes:	Chrome
Product Type:	Contemporary
Construction:	Body is of Brass Construction
Cartridge Type:	Thermostatic
Supply:	Suitable for all plumbing systems preferably balanced
Inlet Connections:	15mm Compression Elbows
Outlet Connections:	G1/2"
Water Pressure:	Min 0.1 bar Max. 5.0 bar
Dimensions:	110-155mm inlet centres



#### Additional Information

- Single Lever Control – flow and temperature are controlled by an easily operated single lever handle
- Thermostatic cartridge maintains showering temperature to +/- 1 degree
- Automatic shut-off in the event of hot or cold water supply failure, thus reducing the risk of injury
- Factory set to a maximum of 43oC to eliminate the ability to select on unsafe temperature. Can be adjusted to user preference.
- Uses swivel inlet elbows with 110-155m centres. Valve can be fed from top, bottom or rear
- Chrome plated to BS EN 248

#### Flow Rates (litres per minute)

System Pressure	0.1bar	0.2bar	0.5bar	1.0bar	2.0bar	3.0bar	5.0bar
Through Handset with Flow Regulators (Both Spray Setting)	---	---	5.3	7.9	11.9	14.6	13.8
Through Handset without Flow Regulators (Both Spray Setting)	0.8	2.7	5.3	7.9	11.8	15.2	19.6

**Technical Advice:** For further information please call 0844 7016273 or email [customer care@bristan.com](mailto:customer care@bristan.com)

**Guarantee:** 5 years covering manufacturing faults.

WRAS Cert. Number: 1704081

WRAS Expiry Date: 30/04/2022

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG  
 Telephone: 0844 701 6274 Facsimile: 0844 701 6275  
 Web Site: [www.bristan.com](http://www.bristan.com) Email: [enquire@bristan.com](mailto:enquire@bristan.com)

